



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ~ #102-S-0 LUBRICANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +300 DEG.F.
PENETRATION.....	NLGI GRADE #3
THICKENER.....	COLLOIDAL CLAY
FILLER.....	HYDROUS-SILICATES
COLOR.....	PEANUT BUTTER

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

A medium temperature Hydrocarbon and Natural Gas lubricant-sealant for high pressure use in A.P.I. Gate valves and Wellhead Production. Also recommended for Natural Gas Pipelines, Refineries and Gasoline Plants.

Stephen D. Frauenberger, President – Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Company – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**