



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #103 LUBRICANT/SEALANT

| | |
|--------------------------|---|
| DROPPING POINT..... | NON-DROPPING |
| BASE OIL..... | SYNTHETIC |
| SHELF LIFE..... | 5-YEARS (CONTROLLED ENVIROMENT) |
| OXIDATION STABILITY..... | GOOD |
| TEMPERATURE RANGE..... | -40 DEG.F.TO +300 DEG.F. |
| PENETRATION..... | NLGI GRADE #3 (ASTM D-217 = 220-250) |
| THICKENER..... | HYDRATED SILICATE |
| FILLER..... | HYDROUS-SILICATES, *TEFLON |
| COLOR..... | RED |

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
*DUPONT TRADEMARK
Manufactured /Country of Origin – U.S.A.

A medium temperature Hydrocarbon and Natural Gas lubricant-sealant for high pressure use in A.P.I. Gate valves and Wellhead Production. Also recommended for Natural Gas Pipelines, Refineries and Gasoline Plants. Climax #103 contains Microfine-Teflon for improved Lubricating and Sealing Capabilities.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**