



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET - #1034-MT LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC-POLYESTER
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-20 DEG.F.TO +400 DEG.F.
PENETRATION.....	NLGI GRADE #3.5 (ASTM D-217 = 200-230)
THICKENER.....	INORGANIC
COLOR.....	CREAM
ADDITIVE/FILLER.....	*MICRONIZED-PTFE

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
MANUFACTURED / COUNTRY OF ORIGIN – U.S.A.
* DuPont Trademark

In addition to a general purpose sealant for liquid and gaseous aliphatic hydrocarbon service; (for example: wet or dry natural gas), this sealant has excellent resistance to internal combustion fuels: regular, premium and high octane gasolines- including oxygenated and reformulated fuels, jet fuels, aviation gasoline, kerosene, fuel blending ingredients; such as alkylate and platformate, fuel and lubricating oils, mixtures of these products and water in all proportions.* Contains Microfine Teflon for added sealing capability for: worn, scored or leaky plug/ball valves.

ASTM D-942 : 0-5 LB. PSI DROP-EXCELLENT
ASTM D-1264: INSOLUBLE IN H2O (WATER)
ASTM D-92: ABOVE 400 DEG.F. (NON-DROPPING)

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**