



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ON #107 PAC-EZ

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +650 DEG.F.
PENETRATION.....	N/A
THICKNER.....	INORGANIC, RHEOLOGICAL ADDITIVE
FILLER.....	GRAPHITE, MOLYBDENUM-DISULFIDE HYDRATED SILICATES
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

Climax 107 Pac-Ez exhibits high temperature and no-melt capabilities that take over in temperature ranges where other stem packings cease to be effective. The principle services include: Asphalt plants, Gas lifts, Hot oil, High temp. steam, Hot hydrocarbon gases / vapors, Salt water brine, Tars and Pitch.

Stephen D. Frauenberger, President – Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Company

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**