



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #108 LUBRICANT/SEALANT

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +650 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #3 (ASTM D-217 = 220-250)
THICKENER.....	INORGANIC
COLOR.....	BLACK
FILLER.....	MILLED FIBER MOLYBDENUM- DISULFIDE HYDROUS-SILICATES
ADDITIVES.....	HYDROGEN SULFIDE SUPPRESSOR / OXIDATION & CORROSION INHIBITOR
NON TOXIC-HAZARDOUS MATERIAL	
FLASH POINT ABOVE 400 DEG.F.	
NON FLAMMABLE	

An all purpose High Temperature Hydrocarbon and Natural Gas Lubricant-Sealant for high pressure use in A.P.I. gate valves and wellhead production. Also recommended for Sour gases and Sour crude oils in production pipeline and refining. Other services include: Natural gas plants, Gasoline plants and Petrochemical plants.

Stephen D. Frauenberger – President, Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co.-U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**