



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ #1500 ANTICEEZE/LUBRICANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (Controlled Environment)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	-20 DEG F. TO 1500 DEG. F.
PENETRATION.....	NLGI GRADE #2.5
THICKENER.....	INORGANIC-CALCIUM SOAP
FILLER.....	ALUMINUM POWDER GRAPHITE MOLY
COLOR.....	SILVER

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin – U.S.A.

Climax Anticeeze 1500 will not gum or harden and is chemically resistant to gas. This compound offers the following: Superior Sealing Capabilities, Non-melting Characteristics, Adhesion to Metals, Great Film Strength and Excellent Antigalling Properties. Uses include: Fuel Injection and Air Starting Valves, Valve Gauges, Compressor Cages, Cylinder Head Gaskets and Studs, Valves and Valve Stems, Plugs, Valve Shafts and Assemblies, Conveyors, Gear Reducers, Transmission Shafts, Fans, Blowers, Compressors, Pumps, Turbines, Etc.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**