



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET~ #400 LUBRICANT/SEALANT

DROPPING POINT.....	NON DROPPING
BASE OIL.....	PETROLEUM DERIVATIVE
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +450 DEG.F.
PENETRATION.....	NLGI GRADE #2 (ASTM D-217 = 265-295)
THICKENER.....	RHEOLOGICAL ADDITIVE
COLOR.....	RED

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin – U.S.A.

This sealant has excellent tack and adhesion and is specifically formulated for Acids and Caustics: Alkalies, Aluminum Chlorides and Hydroxides, Ammonia(Gas or Liquid), Ethylene Oxide, Acetylene Gas, Fats, Glycols, Water and most Aqueous chemical solutions.

Stephen D. Frauenberger, President - Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**