



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ #450 LUBRICANT/SEALANT

DROPPING POINT.....	NON DROPPING
BASE OIL.....	PETROLEUM DERIVATIVE
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE #2 (ASTM D-217 = 265-295)
(STICK).....	NLGI GRADE #6 (ASTM D-217 = 85-115)
THICKENER.....	RHEOLOGICAL ADDITIVE
COLOR.....	WHITE

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE

This sealant has excellent tack and adhesion and offers very good resistance to Aqueous Solutions of Acids and Caustics: Alcohols, Alkalies, Aluminum Chlorides/Hydroxides, Ammonia(Gas or Liquid), Amines, Calcium Solutions, Ethylene Oxide, Fats, Glycerine, Glycols, Soap and Water. Food and pharmaceutical applications as determined suitable by the user.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**