



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ # 525 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC TRIARYL-PHOSPHATE
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	0 DEG.F.TO +400 DEG.F.
PENETRATION (BULK).....	NLGI GRADE # 3 (ASTM D-217 = 220-250)
(STICK).....	NLGI GRADE # 6 (ASTM D-217 = 85-115)
THICKENER.....	INORGANIC
COLOR.....	TRANSLUCENT

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE

This Lubricant is formulated for Air Fractionation and Air Valves. This material is Fire Resistant / Non-Explosive in Air Valve Services and is recommended for the following: Petrochemical, Refining, Air Instruments, Chemical Oxidation, Natural Gas Transmission, Steam Power Generation, Steel Making and General Pneumatic Equipment.

Stephen D. Frauenberger, President - Sales/Manufacturing
E-Mail: sales@climaxlube.com
Climax Lubricants & Equipment Co.- U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**