



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ #800 LUBRICANT/SEALANT

DROPPING POINT.....NON -DROPPING

BASE OIL.....SYNTHETIC

SHELF LIFE.....5-YEARS
(CONTROLLED ENVIROMENT)

OXIDATION STABILITY.....GOOD

TEMPERATURE RANGE.....-20 DEG.F.TO +450 DEG.F.

PENETRATION (BULK).....NLGI GRADE #3
(ASTM D-217 = 220-250)

(STICK).....NLGI GRADE # 6
(ASTM D-217 = 85-115)

THICKENER.....INORGANIC

COLOR.....WHITE

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured /Country of Origin – U.S.A.

Climax 800 can be used for a wide range of Hydrocarbons and Aromatics. Recommended for these principle services: Aniline, Carbon Tetrachloride, Butadiene, Butane, Chloropentane, Ethane, Ethylene, Methane, Methylene Chloride, Naphthas, Hexane, Isobutane, Propane (Wet or Dry), Propylene, Rubber Solvents and Styrene.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**