



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET- #900 LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5-YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-40 DEG.F.TO +650 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM D-217 = 220-250)
THICKENER.....	INORGANIC
FILLER.....	MOLYBDENUM-DISULFIDE
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE  
Manufactured / Country of Origin - U.S.A.

An all purpose High Temperature Hydrocarbon and Natural Gas lubricant. Recommended for Natural Gas Pipelines, Refineries, Gasoline Plants, Petrochemical Plants, Crude Oil Production, Rubber Plants, Compressor Discharge Valves, Dehydrator Valves, Steel Mills and Tailing Systems. The material is suitable for use in Plug Valves,Ball Valves and API Gate Valves; both as a body fill and seat lubricant.

Stephen D. Frauenberger, President – Sales/Manufacturing  
E-Mail: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co.-U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**