



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET - #960-MT LUBRICANT/SEALANT

DROPPING POINT.....	NON -DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-30 DEG.F.TO +450 DEG.F.
PENETRATION.....	NLGI GRADE #3 (ASTM D-217 =220-250)
FILLER.....	*MICRONIZED-PTFE
THICKENER.....	INORGANIC
COLOR.....	WHITE

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
*DUPONT TRADEMARK
Manufactured / Country of Origin – U.S.A.

In addition to excellent service as a general purpose sealant for liquid and gaseous aliphatic hydrocarbons, this sealant has excellent resistance to internal combustion fuels, gasolines, jet fuels, refinery and petrochemical blends, propylenes, benzenes, toluenes, butadienes, xylenes, styrenes, cumenes and other LPG`S.

This particular sealant is made from High Viscosity Polymers and contains Microfine-Teflon (Lubegrade) offering excellent sealing capabilities.

Stephen D. Frauenberger, President - Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. - U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**