



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ON #FL-5 PAC-EZ

DROPPING POINT.....	NON-DROPPING
BASE OIL.....	FLUOROCARBON
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	0 DEG.F.TO +400 DEG.F.
PENETRATION.....	N/A
THICKENER.....	INORGANIC
FILLER.....	*TEFLON – MICROFINE TO PARTICLE SIZE
COLOR.....	TRANSLUCENT

NON TOXIC-HAZARDOUS MATERIAL

FLASH POINT ABOVE 400 DEG.F.

NON FLAMMABLE

*Dupont Trademark

Climax FL-5 is a stem packing formulated primarily for Hazardous Environments. FL-5 is Non-Reactive to Corrosive Liquids and Oxidizing Agents such as Chlorine, Anhydrous Hydrogen Chloride, Nitric Acid, Oxygen, Hydrogen Peroxide and Sulfuric Acid. This material is Thermally stable to 260 DEG.C,(500 DEG.F). Due to the absence of hydrogen in this polymer of Trifluorovinylchloride, this is a completely non-flammable product. FL-5 is an excellent non-reactive stem packing for API Gate Valves, Rockwell hyperseals, Orbit Ball Valves, Pump Packings and any packing application used in manufacturing and the Handling and Transfer of any Highly Corrosive or Oxidizing Materials. Caution: Do Not Use On Aluminum Or Magnesium Parts!

Stephen D. Frauenberger, President – Sales/Manufacturing

Email: sales@climaxlube.com

Climax Lubricants & Equipment Co. – U.S.A

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**