



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET~ S-100 LUBRICANT

DROPPING POINT.....	+400 DEG.F.
BASE OIL.....	PETROLEUM DERIVATIVE
SHELF LIFE.....	5 YEARS (CONTROLLED ENVIROMENT)
OXIDATION STABILITY.....	EXCELLENT
TEMPERATURE RANGE.....	0 DEG.F.TO +400 DEG.F.
PENETRATION.....	NLGI GRADE #2.5 (ASTM D-217 = 245-275)
THICKENER.....	LITHIUM SOAP
FILLER.....	ALUMINUM POWDER
COLOR.....	SILVER

NON TOXIC-HAZARDOUS MATERIAL
FLASH POINT ABOVE 400 DEG.F.
NON FLAMMABLE
Manufactured/Country of Origin - U.S.A.

S-100 Lubricant is a Premium quality high temperature bearing lubricant with a Timken Bearing Test of +50. S-100 offers excellent lubricating characteristics with good water resistance; will not harden, oxidize or cake stem. This lubricant can be applied to the following: bushings stem bearings and threads on all types of gate valves, swivel joints and any industrial lubricant application to 400 DEG.F.

Stephen D. Frauenberger, President – Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**