



## Climax Lubricants & Equipment Co.

### CLIMAX SPEC SHEET ~ VALVE TURN #1 LUBRICANT

DROPPING POINT.....	NON DROPPING
BASE OIL.....	5-YEARS (Controlled Environment)
SHELF LIFE.....	INDEFINITE
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-20 DEG.F. TO +500 DEG.F.
PENETRATION.....	NLGI GRADE #2.5
THICKENER.....	INORGANIC
FILLER.....	MOLYBDENUM-DISULFIDE
COLOR.....	BLACK

NON TOXIC-HAZARDOUS MATERIAL  
FLASH POINT ABOVE 400 DEG.F.  
NON FLAMMABLE

Valve Turn #1 is designed for Hard To Operate Valves and to Work out Valve Residues left in Plug Valves. VT #1 is resistant to Hydrocarbons, LPG'S and Natural Gas. When desired or original torque is achieved an appropriate valve lubricant/sealant should be injected to replace the VT#1 according to Flow media (Service), Temperature Gradient and type(condition) of valve ect.....If desired torque is achieved, along with desired valve performance, VT # 1 can be used for general maintenance. VT # 1 is useful in low temperature applications as well.....

Stephen D. Frauenberger, President - Sales/Manufacturing  
Email: [sales@climaxlube.com](mailto:sales@climaxlube.com)  
Climax Lubricants & Equipment Co. – U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012  
713-923-2626 – Fax 713-928-9025 - [climaxlube@aol.com](mailto:climaxlube@aol.com)**