



Climax Lubricants & Equipment Co.

CLIMAX SPEC SHEET ~ VCM

DROPPING POINT.....	NON DROPPING
BASE OIL.....	SYNTHETIC
SHELF LIFE.....	UNDETERMINED
OXIDATION STABILITY.....	GOOD
TEMPERATURE RANGE.....	-10 DEG.F. TO +400 DEG.F.
PENETRATION.....	NLGI #1.5
THICKENER.....	VINYL POLYMER
FILLER.....	MOLYVAN-A
COLOR.....	AMBER
NON TOXIC-HAZARDOUS MATERIAL(DOES NOT CONTAIN OZONE DEPLETING SUBSTANCE)	
FLASH POINT ABOVE 225 DEG.F.	
NON FLAMMABLE	

VALVE CLEANER/SOLVENT

Climax VCM is a penetrant-gel formulated to dissolve or soften the hardened or dried lubricants, lacquer and residual gum deposits in a valve which will make it hard to operate.

VCM is not designed to be used as a lubricant/sealant. Use as much of this product as the valve will take (NO MORE THAN RECOMMENDED VALVE CAPACITY), then wait 20 minutes and try to operate the valve. If the valve will turn, work it back and forth to make sure the product can get into all the passages and around the plug. If after first application the valve will not turn, wait 20 minutes, then repeat the application. When the valve(s) operate freely a recommended lubricant should be pumped into the valve to replace the VCM.

Climax VCM is available in 8 oz. polypacks for use in hydraulically assisted grease guns. Also available in 14 1/2 oz. grease gun cartridges, 5-qt.(10-lbs.) cans and 5 or 6 gallon(35-40 lbs.) pails.

CAUTION: Application to some rubber types (buna-viton,i.e."O"-rings) may cause swelling or disfiguration of material. Not recommended for soft seat valves.

Stephen D. Frauenberger, President-Sales/Manufacturing
Email: sales@climaxlube.com
Climax Lubricants & Equipment Co. – Houston, Texas U.S.A.

**P.O. Box 5235 – Houston, Texas U.S.A. 77262-5235 – 7915 East Elm Street – 77012
713-923-2626 – Fax 713-928-9025 - climaxlube@aol.com**